

屋内照明器具特性

品番 (品名)	L S E W 2 0 2 7														
光源	LLD4300N ×1 930.0 l m														
管理番号	K0165622 (0) DB 1														
B Z 分類	B Z 5														

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	3 %																			
下方光束	73 %																			
室指数	照明率 (X 0.01)																	Z C M		
保守率	良 中 否 0.63 0.6 0.56	0.6	42	33	27	22	41	32	26	22	39	31	26	22	37	30	25	22	20	
		0.8	49	40	34	30	48	40	34	30	46	38	33	29	43	37	32	29	27	
		1.0	54	46	40	35	53	45	39	35	50	43	38	34	48	42	37	34	32	
		1.25	59	51	45	41	57	50	45	40	54	48	44	40	52	47	42	39	37	
下方投影面積	c m ²	1.5	62	55	49	45	60	54	49	44	57	52	47	44	55	50	46	43	41	
		2.0	66	60	55	51	64	59	54	50	61	57	53	50	59	55	51	49	46	
取付高さ	器具間隔最大限		2.5	69	63	59	55	67	62	58	55	64	60	57	54	61	58	55	52	50
	横方向 (A)	縦方向 (B)	3.0	71	66	62	59	69	65	61	58	66	63	59	57	63	60	58	55	53
H m	1.26 H m	1.26 H m	4.0	73	69	66	63	71	68	65	62	69	66	63	61	66	64	61	59	57
			5.0	74	71	68	66	73	70	67	65	70	68	66	64	68	66	64	62	59
			7.0	76	74	72	70	75	73	71	69	72	70	69	67	70	68	67	65	62
			10.0	78	76	74	73	76	75	73	72	74	72	71	70	71	70	69	68	65

