

# 屋内照明器具特性

品番 (品名)	L S E W 2 0 3 0	
光源	LLD4300L ×1	930.0 l m
管理番号	K0165624 ( 0 ) DB 1	
B Z 分類	B Z 5	

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束		3 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
	下方光束		65 %		床	10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X 0 . 0 1 )																			Z C M		
保守率	良	0.63	0.6	3.7	2.9	2.4	2.0	3.6	2.9	2.3	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	1.9	1.8		
	中	0.6	0.8	4.4	3.6	3.1	2.7	4.3	3.5	3.0	2.7	4.1	3.4	3.0	2.6	3.9	3.3	2.9	2.6	2.4		
	否	0.56	1.0	4.8	4.1	3.6	3.2	4.7	4.0	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.0	2.9		
	下方投影面積	c m <sup>2</sup>		1.25	5.2	4.6	4.0	3.6	5.1	4.5	4.0	3.6	4.9	4.3	3.9	3.6	4.6	4.2	3.8	3.5	3.3	
取付高さ	器具間隔最大限		H m	1.26 H m	縦方向 ( B )	1.26 H m	2.5	6.1	5.7	5.3	4.9	6.0	5.6	5.2	4.9	5.7	5.4	5.1	4.8	4.5		
	横方向 ( A )	3.0					6.3	5.9	5.5	5.2	6.2	5.8	5.5	5.2	5.9	5.6	5.3	5.1	5.7	5.4	5.2	5.0
等価発光面積	c m <sup>2</sup>		2.0	5.9	5.4	4.9	4.6	5.8	5.3	4.9	4.5	5.5	5.1	4.7	4.4	5.3	4.9	4.6	4.3	4.1		
	H m	1.26 H m	縦方向 ( B )	1.26 H m	4.0	6.5	6.2	5.9	5.6	6.4	6.1	5.8	5.6	6.1	5.9	5.6	5.4	5.9	5.7	5.5	5.3	5.1
					5.0	6.7	6.4	6.1	5.9	6.5	6.3	6.0	5.8	6.3	6.1	5.9	5.7	6.0	5.9	5.7	5.5	5.3
					7.0	6.8	6.6	6.4	6.2	6.7	6.5	6.3	6.1	6.5	6.3	6.1	6.0	6.2	6.1	6.0	5.8	5.6
10.0	6.9	6.8	6.6	6.5	6.8	6.7	6.5	6.4	6.6	6.5	6.3	6.2	6.4	6.3	6.2	6.1	6.0	5.8	5.6	5.4		

