

# 屋内照明器具特性

品番 (品名)	L S E W C 4 0 7 3														
光源	LED2700_70_175 x1 175.0 l m														
管理番号	K0171394 ( 0 ) DB 1														
B Z 分類	B Z 6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	51 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	49 %		室指数	照明率 ( X0.01 ) Z C M																
保守率	良 中 否 0.63 0.6 0.56	0.6	48	36	29	24	44	34	27	22	37	29	23	19	30	24	20	17	11	
		0.8	57	46	38	32	52	42	35	30	44	36	31	26	36	30	26	23	16	
		1.0	63	52	45	39	58	48	42	37	48	41	36	32	40	34	30	27	19	
		1.25	68	59	51	46	63	54	48	43	53	46	41	37	43	39	35	31	22	
下方投影面積	c m <sup>2</sup>	1.5	72	63	56	51	67	59	53	48	56	50	45	41	46	42	38	35	25	
		2.0	78	70	64	59	72	65	60	55	60	55	51	47	50	46	43	40	29	
取付高さ	器具間隔最大限		2.5	81	74	69	64	75	69	64	60	63	59	55	52	52	49	46	44	31
	横方向 ( A )	縦方向 ( B )	3.0	83	78	73	68	77	72	68	64	65	61	58	55	54	51	49	47	33
H m	1.37 H m	1.25 H m	4.0	87	82	78	74	80	76	72	69	68	65	62	60	57	54	52	50	36
			5.0	88	85	81	78	82	79	75	73	70	67	65	62	58	56	54	53	38
			7.0	91	88	85	82	84	82	79	77	72	70	68	66	60	58	57	56	40
			10.0	93	90	88	86	86	84	82	80	73	72	71	69	61	60	59	58	42

