

# 屋内照明器具特性

|         |                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XSLG105LS                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED2700_70_360 x1 360.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0171432(0)DB1             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ9/0.9/BZ8                |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|                  |                                    |          |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|------------------|------------------------------------|----------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率             | 100%                               | 天井       | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |    |
|                  |                                    |          | 反射率             | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
|                  |                                    |          |                 | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 上方光束<br>下方光束     | 50%<br>50%                         | 室指数      | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 保守率              | 良<br>中<br>否<br>0.63<br>0.6<br>0.56 | 0.6      | 4.4             | 3.2 | 2.4 | 1.8 | 4.0 | 2.9 | 2.2 | 1.7 | 3.3 | 2.4 | 1.8 | 1.4 | 2.6 | 2.0 | 1.5 | 1.1 | 0.6 |     |    |
|                  |                                    | 0.8      | 5.3             | 4.0 | 3.2 | 2.6 | 4.8 | 3.7 | 3.0 | 2.4 | 3.9 | 3.1 | 2.5 | 2.0 | 3.1 | 2.5 | 2.0 | 1.6 | 0.9 |     |    |
|                  |                                    | 1.0      | 5.9             | 4.7 | 3.8 | 3.2 | 5.4 | 4.3 | 3.5 | 3.0 | 4.4 | 3.6 | 3.0 | 2.5 | 3.5 | 2.9 | 2.4 | 2.0 | 1.2 |     |    |
|                  |                                    | 1.25     | 6.4             | 5.3 | 4.5 | 3.8 | 5.9 | 4.9 | 4.1 | 3.5 | 4.8 | 4.1 | 3.5 | 3.0 | 3.9 | 3.3 | 2.8 | 2.4 | 1.5 |     |    |
| 下方投影面積<br>等価発光面積 | c m <sup>2</sup>                   | 1.5      | 6.8             | 5.8 | 5.0 | 4.3 | 6.2 | 5.3 | 4.6 | 4.0 | 5.1 | 4.4 | 3.9 | 3.4 | 4.1 | 3.6 | 3.2 | 2.8 | 1.8 |     |    |
|                  |                                    | 2.0      | 7.4             | 6.5 | 5.7 | 5.1 | 6.8 | 6.0 | 5.3 | 4.8 | 5.6 | 5.0 | 4.5 | 4.0 | 4.5 | 4.1 | 3.7 | 3.3 | 2.2 |     |    |
|                  |                                    | 2.5      | 7.8             | 7.0 | 6.3 | 5.7 | 7.1 | 6.4 | 5.8 | 5.3 | 5.9 | 5.4 | 4.9 | 4.5 | 4.8 | 4.4 | 4.0 | 3.7 | 2.5 |     |    |
| 取付高さ             | 器具間隔最大限                            |          | 3.0             | 8.0 | 7.3 | 6.7 | 6.2 | 7.4 | 6.7 | 6.2 | 5.7 | 6.2 | 5.7 | 5.2 | 4.8 | 5.0 | 4.6 | 4.3 | 4.0 | 2.7 |    |
|                  | 横方向 (A)                            | 縦方向 (B)  | 4.0             | 8.4 | 7.8 | 7.2 | 6.8 | 7.7 | 7.2 | 6.7 | 6.3 | 6.5 | 6.1 | 5.7 | 5.4 | 5.3 | 5.0 | 4.7 | 4.4 | 3.0 |    |
| H m              | 1.59 H m                           | 2.09 H m | 5.0             | 8.6 | 8.1 | 7.6 | 7.2 | 7.9 | 7.5 | 7.1 | 6.7 | 6.7 | 6.3 | 6.0 | 5.7 | 5.5 | 5.2 | 5.0 | 4.7 | 3.3 |    |
|                  |                                    |          | 7.0             | 8.9 | 8.5 | 8.1 | 7.8 | 8.2 | 7.9 | 7.5 | 7.2 | 6.9 | 6.7 | 6.4 | 6.2 | 5.7 | 5.5 | 5.3 | 5.1 | 3.6 |    |
|                  |                                    |          | 10.0            | 9.1 | 8.8 | 8.5 | 8.2 | 8.4 | 8.2 | 7.9 | 7.7 | 7.2 | 6.9 | 6.7 | 6.5 | 6.0 | 5.8 | 5.6 | 5.5 | 3.9 |    |

