

屋内照明器具特性

品番 (品名)	XSLG106LS															
光源	LED2700_70_220 x1 220.0 1m															
管理番号	K0169179(0)DR1															
BZ分類	BZ5/0.7/BZ4															

器具効率	100%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
		床	10%				10%				10%				10%				0%
上方光束	50%	室指数																	
下方光束	50%	照明率 (X0.01) ZCM																	
保守率	良 中 否 0.63 0.6 0.56	0.6	50	39	32	27	47	37	30	26	39	32	26	23	33	27	23	20	15
		0.8	60	49	42	37	55	46	39	35	47	40	35	31	39	34	30	27	21
		1.0	66	56	49	44	61	53	46	42	52	46	41	37	44	39	35	32	25
		1.25	72	63	56	51	66	59	53	48	57	51	46	43	48	43	40	37	29
下方投影面積	c m ²	1.5	75	67	61	56	70	63	58	53	60	55	50	47	50	47	43	41	31
		2.0	81	74	69	64	75	69	64	60	64	60	56	53	54	51	48	46	35
等価発光面積	c m ²	2.5	84	78	73	69	78	73	69	65	67	63	60	57	56	54	51	49	38
		3.0	86	81	77	73	80	76	72	69	69	66	63	60	58	56	54	52	39
取付高さ	器具間隔最大限		4.0	89	85	82	78	83	79	76	74	71	69	66	64	60	58	57	42
	横方向 (A)	縦方向 (B)	5.0	91	87	84	82	84	82	79	77	73	71	69	67	61	60	59	43
H m	0.00 H m	1.67 H m	7.0	92	90	88	86	86	84	82	80	74	73	71	70	63	62	61	45
			10.0	94	92	91	89	88	86	85	83	76	75	73	72	64	63	63	47

