

屋内照明器具特性	
品番 (品名)	L G W C 8 0 3 0 6 K
光源	LED2700_70_348 ×1 348.0 l m
管理番号	K0149620 (0) DR 1
B Z 分類	B Z 9

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		50 % 50 %	室指数	照明率 (X0.01)																Z C M	
保守率		良 中 否	0.63	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	19	14	11	6
			0.6	0.8	52	40	32	25	48	37	29	23	39	30	24	20	31	25	20	16	9
			0.56	1.0	58	46	38	31	53	43	35	29	44	35	29	24	35	28	24	20	12
			1.25	1.25	64	53	44	38	58	48	41	35	48	40	34	29	38	32	28	24	15
下方投影面積		c m ²	1.5	68	57	49	43	62	53	46	40	51	44	38	33	41	36	31	27	17	
等価発光面積			c m ²	2.0	74	64	57	51	67	59	53	47	56	50	44	40	45	40	36	33	21
取付 高さ	器具間隔最大限			2.5	77	69	62	56	71	64	58	52	59	53	49	44	48	44	40	37	24
	横方向 (A)		縦方向 (B)	3.0	80	73	66	61	74	67	61	57	61	56	52	48	50	46	43	40	27
H m	1.88 H m		1.63 H m	4.0	83	77	72	67	77	72	67	62	65	60	57	53	53	50	47	44	30
				5.0	86	81	76	72	79	75	70	66	67	63	60	57	55	52	50	47	33
				7.0	89	84	81	77	82	78	75	72	69	67	64	61	57	55	53	51	36
				10.0	91	88	85	82	84	81	79	76	72	69	67	65	60	58	56	55	39

