

屋内照明器具特性

品番 (品名)	NNF 2 6 9 1 1 C														
光源	LED3000_70_4080 x1 4080.0 1 m														
管理番号	K0171119 (2) D 1														
BZ分類	BZ6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		15 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		85 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.69	0.6	5.2	3.9	3.1	2.5	4.9	3.8	3.0	2.5	4.6	3.5	2.9	2.4	4.2	3.3	2.7	2.3	2.0	
	中	0.67	0.8	6.1	4.9	4.0	3.4	5.8	4.7	3.9	3.3	5.4	4.4	3.7	3.2	5.0	4.1	3.5	3.1	2.7	
	否	0.63	1.0	6.7	5.5	4.7	4.1	6.4	5.4	4.6	4.0	5.9	5.0	4.4	3.8	5.5	4.7	4.1	3.7	3.3	
			0.63	1.25	7.3	6.2	5.4	4.8	7.0	6.0	5.3	4.7	6.5	5.6	5.0	4.5	6.0	5.3	4.7	4.3	3.8
下方投影面積			c m ²																		
			c m ²																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
1.5m	2.09 m	2.13 m	4.0	9.2	8.7	8.2	7.8	8.9	8.4	8.0	7.6	8.3	7.9	7.5	7.2	7.8	7.4	7.1	6.8	6.2	
2	2.76	2.7	5.0	9.5	9.0	8.6	8.2	9.1	8.7	8.3	8.0	8.6	8.2	7.9	7.6	8.0	7.7	7.4	7.2	6.6	
2.5	3.43	3.28	7.0	9.7	9.4	9.0	8.7	9.4	9.1	8.8	8.5	8.8	8.6	8.3	8.1	8.3	8.1	7.8	7.6	7.0	
3	4.09	3.88	10.0	9.9	9.6	9.4	9.1	9.6	9.4	9.1	8.9	9.1	8.8	8.6	8.5	8.5	8.3	8.2	8.0	7.3	

