

屋内照明器具特性

品番 (品名)	LGS1030N		
光源	LED5000_70_450 ×1	450.0 1m	
管理番号	K0161677(0)DR1		
BZ分類	BZ1/1.1/BZ2/8.5/BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	73	64	59	55	72	64	58	55	70	63	58	55	68	62	58	55	53	
	中 0.63	0.8	80	72	67	63	79	72	67	63	77	71	66	63	75	70	66	63	61	
	否 0.56	1.0	85	78	73	69	84	78	73	69	82	76	72	69	80	75	71	68	67	
下方投影面積	cm ²	1.25	90	83	79	75	88	83	78	75	86	81	77	74	84	80	76	74	72	
		1.5	93	87	83	79	91	86	82	79	89	85	81	78	87	83	80	78	76	
等価発光面積	cm ²	2.0	96	92	88	85	95	91	88	85	93	89	86	84	91	88	85	83	81	
		2.5	99	95	92	89	98	94	91	88	95	92	90	87	93	91	88	86	84	
取付高さ	器具間隔最大限		3.0	100	97	94	92	99	96	93	91	97	94	92	90	95	92	91	89	87
Hm	横方向 (A)	縦方向 (B)	4.0	102	100	97	95	101	99	97	95	99	97	95	93	97	95	93	92	90
	0.47Hm	0.47Hm	5.0	103	101	99	98	102	100	99	97	100	98	97	95	98	96	95	94	92
			7.0	105	103	102	100	104	102	101	100	101	100	99	98	99	98	97	96	94
			10.0	106	105	104	103	105	103	103	102	102	101	101	100	100	99	99	98	95

