

屋内照明器具特性

| | | |
|---------|--------------------|----------|
| 品番 (品名) | XAS3382N | |
| 光源 | LED5000_70_1340 ×1 | 1340.0lm |
| 管理番号 | K0171370(0)D 1 | |
| BZ分類 | BZ1/3.5/BZ2 | |

| | | | | | | | | | | | | | | | | | | | | |
|----------------|--------------------|--------------------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 42% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 58% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 64 | 56 | 51 | 47 | 61 | 54 | 49 | 46 | 55 | 50 | 46 | 43 | 50 | 46 | 43 | 41 | 37 |
| | 中 | 0.63 | 0.8 | 71 | 63 | 58 | 54 | 67 | 60 | 56 | 52 | 60 | 55 | 52 | 49 | 54 | 50 | 48 | 45 | 40 |
| | 否 | 0.56 | 1.0 | 76 | 68 | 63 | 59 | 71 | 65 | 60 | 57 | 64 | 59 | 56 | 53 | 57 | 53 | 51 | 49 | 42 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 80 | 73 | 68 | 64 | 75 | 69 | 65 | 61 | 67 | 63 | 59 | 57 | 59 | 56 | 54 | 52 | 44 |
| | | | 1.5 | 82 | 76 | 72 | 68 | 78 | 72 | 68 | 65 | 69 | 65 | 62 | 60 | 61 | 58 | 56 | 54 | 46 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 88 | 84 | 80 | 77 | 83 | 80 | 76 | 74 | 74 | 71 | 69 | 67 | 65 | 63 | 61 | 60 | 49 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 90 | 86 | 83 | 80 | 85 | 82 | 79 | 76 | 75 | 73 | 70 | 69 | 66 | 64 | 63 | 61 | 50 |
| H _m | 0.41H _m | 0.41H _m | 4.0 | 92 | 89 | 86 | 84 | 87 | 84 | 82 | 80 | 77 | 75 | 73 | 71 | 67 | 66 | 65 | 63 | 52 |
| | | | 5.0 | 93 | 91 | 89 | 86 | 88 | 86 | 84 | 82 | 78 | 76 | 75 | 73 | 68 | 67 | 66 | 65 | 53 |
| | | | 7.0 | 95 | 93 | 91 | 89 | 89 | 88 | 86 | 85 | 79 | 78 | 77 | 76 | 69 | 68 | 67 | 67 | 54 |
| | | | 10.0 | 96 | 95 | 93 | 92 | 91 | 89 | 88 | 87 | 80 | 79 | 78 | 77 | 70 | 69 | 69 | 68 | 54 |

