

屋内照明器具特性	
品番 (品名)	L G W C 4 7 0 2 2
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 7 6 3 4 7 (0) D R 1
B Z 分類	B Z 1

器具効率	9 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束	9 6 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束																				
保守率	良 中 否	0 . 6 3	0 . 6	8 2	7 6	7 3	7 0	8 1	7 6	7 2	7 0	8 0	7 5	7 2	7 0	7 9	7 5	7 2	7 0	6 9
		0 . 6	0 . 8	8 7	8 2	7 9	7 7	8 7	8 2	7 9	7 6	8 5	8 1	7 8	7 6	8 4	8 0	7 8	7 6	7 5
		0 . 5 6	1 . 0	9 1	8 6	8 3	8 1	9 0	8 6	8 3	8 1	8 8	8 5	8 2	8 0	8 7	8 4	8 2	8 0	7 9
			1 . 2 5	9 4	9 0	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 6	8 4	9 0	8 7	8 5	8 3	8 2
下方投影面積	c m ²		1 . 5	9 5	9 2	8 9	8 7	9 5	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 1	8 9	8 7	8 6	8 4
等価発光面積		c m ²	2 . 0	9 8	9 5	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	9 3	9 1	9 0	8 9	8 7
			2 . 5	9 9	9 7	9 5	9 3	9 8	9 6	9 4	9 3	9 6	9 4	9 3	9 2	9 4	9 3	9 2	9 1	8 9
取付 高さ	器具間隔最大限		3 . 0	1 0 0	9 8	9 6	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 5	9 4	9 3	9 2	9 0
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	1 0 1	1 0 0	9 8	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 6	9 5	9 4	9 4	9 1
			5 . 0	1 0 2	1 0 1	9 9	9 8	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 7	9 6	9 5	9 5	9 2
			7 . 0	1 0 3	1 0 2	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 9	9 9	9 8	9 7	9 7	9 7	9 6	9 6	9 3
			1 0 . 0	1 0 3	1 0 2	1 0 2	1 0 1	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 9	9 8	9 8	9 8	9 7	9 7	9 4

