

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNLK42523J + NNL4300ENT      |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_3200 x1 3200.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0130919 (* ) DB 1           |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |         |         |      |                   |     |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
|--------|---------|---------|------|-------------------|-----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率   | 100 %   | 天井      | 80 % |                   |     |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|        |         |         | 壁    | 70                | 50  | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
| 上方光束   | 4 %     | 反射率     | 床    | 10 %              |     |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
| 下方光束   | 96 %    |         | 室指数  | 照明率 ( X0.01 ) ZCM |     |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率    | 良       | 0.83    | 0.6  | 55                | 42  | 34 | 29   | 53   | 42 | 34 | 29   | 51   | 40 | 33 | 28   | 48   | 39 | 33 | 28  | 26  |
|        | 中       | 0.81    | 0.8  | 65                | 53  | 45 | 39   | 63   | 52 | 44 | 38   | 60   | 50 | 43 | 38   | 57   | 48 | 42 | 37  | 35  |
|        | 否       | 0.77    | 1.0  | 71                | 60  | 52 | 46   | 69   | 59 | 51 | 46   | 66   | 57 | 50 | 45   | 62   | 55 | 49 | 44  | 42  |
|        |         |         | 1.25 | 77                | 67  | 59 | 53   | 75   | 66 | 58 | 53   | 71   | 63 | 57 | 52   | 68   | 61 | 56 | 51  | 48  |
| 下方投影面積 |         |         | 1.5  | 81                | 72  | 65 | 59   | 79   | 70 | 64 | 58   | 75   | 68 | 62 | 57   | 72   | 66 | 60 | 56  | 53  |
| 等価発光面積 |         |         | 2.0  | 87                | 79  | 72 | 67   | 85   | 77 | 71 | 66   | 81   | 75 | 69 | 65   | 77   | 72 | 68 | 64  | 60  |
| 取付高さ   | 器具間隔最大限 |         | 2.5  | 90                | 84  | 78 | 73   | 88   | 82 | 77 | 72   | 85   | 79 | 74 | 70   | 81   | 76 | 72 | 69  | 66  |
|        | 横方向 (A) | 縦方向 (B) | 3.0  | 93                | 87  | 82 | 77   | 91   | 85 | 80 | 76   | 87   | 82 | 78 | 75   | 84   | 80 | 76 | 73  | 69  |
| 1.5m   | 1.99 m  | 2.17 m  | 4.0  | 96                | 91  | 87 | 83   | 94   | 90 | 86 | 82   | 91   | 87 | 83 | 80   | 87   | 84 | 81 | 78  | 75  |
| 2      | 2.62    | 2.74    | 5.0  | 98                | 94  | 90 | 87   | 96   | 93 | 89 | 86   | 93   | 89 | 86 | 84   | 89   | 87 | 84 | 82  | 78  |
| 2.5    | 3.26    | 3.32    | 7.0  | 101               | 97  | 95 | 92   | 99   | 96 | 93 | 91   | 95   | 93 | 90 | 88   | 92   | 90 | 88 | 86  | 82  |
| 3      | 3.89    | 3.92    | 10.0 | 102               | 100 | 98 | 96   | 101  | 99 | 96 | 95   | 97   | 95 | 94 | 92   | 94   | 92 | 91 | 90  | 86  |

