

屋内照明器具特性

品番 (品名)	XLX450DEVP														
光源	LED3500_85_4830 x1 4830.0 lm														
管理番号	K0130919 (*) DB 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	4 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	96 %		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.83	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26
		0.81	0.8	65	53	45	39	63	52	44	38	60	50	43	38	57	48	42	37	35
		0.77	1.0	71	60	52	46	69	59	51	46	66	57	50	45	62	55	49	44	42
			1.25	77	67	59	53	75	66	58	53	71	63	57	52	68	61	56	51	48
下方投影面積	c m ²	1.5	81	72	65	59	79	70	64	58	75	68	62	57	72	66	60	56	53	
		2.0	87	79	72	67	85	77	71	66	81	75	69	65	77	72	68	64	60	
取付高さ	器具間隔最大限		2.5	90	84	78	73	88	82	77	72	85	79	74	70	81	76	72	69	66
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	85	80	76	87	82	78	75	84	80	76	73	69
1.5m	1.99 m	2.17 m	4.0	96	91	87	83	94	90	86	82	91	87	83	80	87	84	81	78	75
2	2.62	2.74	5.0	98	94	90	87	96	93	89	86	93	89	86	84	89	87	84	82	78
2.5	3.26	3.32	7.0	101	97	95	92	99	96	93	91	95	93	90	88	92	90	88	86	82
3	3.89	3.92	10.0	102	100	98	96	101	99	96	95	97	95	94	92	94	92	91	90	86

