

屋内照明器具特性	
品番 (品名)	NY Y 4 0 0 2 3
光源	LED3000_70_1080 x1 1080.0 lm
管理番号	K0171207(0)DB1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	50%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	5.9	5.0	4.4	4.0	5.5	4.7	4.2	3.8	4.9	4.2	3.8	3.5	4.2	3.8	3.5	3.3	2.8
	中	0.67	0.8	6.7	5.8	5.3	4.8	6.3	5.5	5.0	4.6	5.5	4.9	4.5	4.2	4.8	4.4	4.1	3.9	3.2
	否	0.63	1.0	7.2	6.4	5.9	5.5	6.8	6.1	5.6	5.2	5.9	5.4	5.0	4.7	5.1	4.8	4.5	4.3	3.5
			1.25	7.7	7.0	6.5	6.0	7.2	6.6	6.1	5.8	6.2	5.8	5.5	5.2	5.4	5.1	4.8	4.6	3.8
下方投影面積		cm ²	1.5	8.0	7.4	6.9	6.5	7.5	6.9	6.5	6.2	6.5	6.1	5.8	5.5	5.6	5.3	5.1	4.9	4.0
等価発光面積		cm ²	2.0	8.4	7.9	7.5	7.1	7.9	7.4	7.1	6.7	6.8	6.5	6.2	6.0	5.8	5.6	5.4	5.3	4.2
取付高さ	器具間隔最大限		2.5	8.7	8.2	7.9	7.5	8.1	7.7	7.4	7.1	7.0	6.7	6.5	6.3	6.0	5.8	5.7	5.5	4.4
	横方向 (A)	縦方向 (B)	3.0	8.9	8.5	8.1	7.8	8.3	7.9	7.7	7.4	7.1	6.9	6.7	6.5	6.1	6.0	5.8	5.7	4.4
Hm	0.64Hm	0.64Hm	4.0	9.1	8.8	8.5	8.3	8.5	8.2	8.0	7.8	7.3	7.1	7.0	6.8	6.2	6.1	6.0	5.9	4.6
			5.0	9.2	9.0	8.7	8.5	8.6	8.4	8.2	8.0	7.4	7.3	7.1	7.0	6.3	6.2	6.1	6.1	4.7
			7.0	9.4	9.2	9.0	8.8	8.7	8.6	8.4	8.3	7.6	7.4	7.3	7.2	6.4	6.4	6.3	6.2	4.7
			10.0	9.5	9.3	9.2	9.1	8.9	8.7	8.6	8.5	7.6	7.6	7.5	7.4	6.5	6.4	6.4	6.3	4.8

