

屋内照明器具特性

品番 (品名)	XLX465DENP									
光源	LED5000_85_6900 x1					6900.0lm				
管理番号	K0130919(*)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数	照明率 (X0.01)																ZCM		
下方光束	96%																				
保守率	良 中 否	0.83	0.6	5.5	4.2	3.4	2.9	5.3	4.2	3.4	2.9	5.1	4.0	3.3	2.8	4.8	3.9	3.3	2.8	2.6	
		0.81	0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.4	3.8	6.0	5.0	4.3	3.8	5.7	4.8	4.2	3.7	3.5	
		0.77	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.6	6.6	5.7	5.0	4.5	6.2	5.5	4.9	4.4	4.2	
			1.25	7.7	6.7	5.9	5.3	7.5	6.6	5.8	5.3	7.1	6.3	5.7	5.2	6.8	6.1	5.6	5.1	4.8	
下方投影面積 等価発光面積	c m ²	1.5	8.1	7.2	6.5	5.9	7.9	7.0	6.4	5.8	7.5	6.8	6.2	5.7	7.2	6.6	6.0	5.6	5.3		
		2.0	8.7	7.9	7.2	6.7	8.5	7.7	7.1	6.6	8.1	7.5	6.9	6.5	7.7	7.2	6.8	6.4	6.0		
		2.5	9.0	8.4	7.8	7.3	8.8	8.2	7.7	7.2	8.5	7.9	7.4	7.0	8.1	7.6	7.2	6.9	6.6		
取付高さ	器具間隔最大限		3.0	9.3	8.7	8.2	7.7	9.1	8.5	8.0	7.6	8.7	8.2	7.8	7.5	8.4	8.0	7.6	7.3	6.9	
	横方向 (A)	縦方向 (B)																			
1.5m	1.99m	2.17m	4.0	9.6	9.1	8.7	8.3	9.4	9.0	8.6	8.2	9.1	8.7	8.3	8.0	8.7	8.4	8.1	7.8	7.5	
2	2.62	2.74	5.0	9.8	9.4	9.0	8.7	9.6	9.3	8.9	8.6	9.3	8.9	8.6	8.4	8.9	8.7	8.4	8.2	7.8	
2.5	3.26	3.32	7.0	10.1	9.7	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.0	8.8	9.2	9.0	8.8	8.6	8.2	
3	3.89	3.92	10.0	10.2	10.0	9.8	9.6	10.1	9.9	9.6	9.5	9.7	9.5	9.4	9.2	9.4	9.2	9.1	9.0	8.6	

