

屋内照明器具特性

品番 (品名) NTN82430

光源 LDR3L-W-E11 x1 365.0 1m

管理番号 K0174895(3)DR1

BZ分類 BZ1

| 器具効率 | 95% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
|------------------|-----------------|---------|----------------|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|-----|-----|----|----|-----|----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | | |
| 上方光束 | 0% | 反射率 | 壁 | | | | | | | | | | | | | | | | | |
| 下方光束 | 95% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | |
| | | 室指数 | 照明率 (X 0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.67 | 0.6 | 83 | 78 | 75 | 73 | 82 | 78 | 75 | 73 | 81 | 77 | 74 | 72 | 80 | 77 | 74 | 72 | 71 | |
| | 中 0.63 | 0.8 | 88 | 84 | 81 | 79 | 87 | 83 | 81 | 78 | 86 | 83 | 80 | 78 | 85 | 82 | 80 | 78 | 77 | |
| | 否 0.56 | 1.0 | 91 | 87 | 84 | 82 | 90 | 87 | 84 | 82 | 89 | 86 | 84 | 82 | 88 | 85 | 83 | 81 | 80 | |
| 下方投影面積 等価発光面積 | cm ² | 1.25 | 94 | 90 | 88 | 86 | 93 | 90 | 87 | 85 | 91 | 89 | 87 | 85 | 90 | 88 | 86 | 84 | 83 | |
| | | 1.5 | 95 | 92 | 90 | 88 | 94 | 92 | 89 | 88 | 93 | 90 | 89 | 87 | 91 | 89 | 88 | 86 | 85 | |
| | | 2.0 | 97 | 95 | 93 | 91 | 96 | 94 | 92 | 91 | 95 | 93 | 91 | 90 | 93 | 91 | 90 | 89 | 87 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 98 | 96 | 95 | 93 | 97 | 96 | 94 | 93 | 96 | 94 | 93 | 92 | 94 | 93 | 92 | 91 | 89 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 99 | 97 | 96 | 94 | 98 | 97 | 95 | 94 | 96 | 95 | 94 | 93 | 95 | 94 | 93 | 92 | 90 |
| Hm | 0.59Hm | 0.60Hm | 4.0 | 100 | 99 | 97 | 96 | 99 | 98 | 97 | 96 | 97 | 96 | 95 | 94 | 95 | 95 | 94 | 93 | 91 |
| | | | 5.0 | 101 | 100 | 99 | 98 | 100 | 99 | 98 | 97 | 98 | 97 | 96 | 95 | 96 | 95 | 95 | 94 | 92 |
| | | | 7.0 | 101 | 100 | 100 | 99 | 100 | 100 | 99 | 98 | 98 | 98 | 97 | 97 | 96 | 96 | 95 | 95 | 93 |
| | | | 10.0 | 102 | 101 | 101 | 100 | 101 | 100 | 99 | 99 | 98 | 98 | 97 | 97 | 96 | 96 | 96 | 93 | |

