

屋内照明器具特性

品番 (品名)	NTN82430	
光源	LDR3L-M-E11 x1	185.0 lm
管理番号	K0174888(1)DR1	
BZ分類	BZ1	

器具効率	95%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	95%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良 0.67	0.6	0.6	92	89	87	86	91	89	87	86	91	88	87	86	90	88	87	85	85
	中 0.63		0.8	95	92	90	89	94	92	90	89	93	91	90	89	92	91	89	88	88
	否 0.56		1.0	96	94	93	91	96	94	92	91	95	93	92	91	94	92	91	90	90
下方投影面積	cm ²	1.25	98	96	94	93	97	95	94	93	96	95	93	92	95	94	93	92	91	
		1.5	99	97	96	95	98	97	95	94	97	96	94	94	96	95	94	93	92	
等価発光面積	cm ²	2.0	100	99	97	97	99	98	97	96	98	97	96	95	96	96	95	94	93	
		2.5	101	100	99	98	100	99	98	97	98	98	97	96	97	96	96	95	94	
取付高さ	器具間隔最大限		3.0	101	100	99	99	100	100	99	98	99	98	98	97	97	97	96	94	
	横方向 (A)	縦方向 (B)	4.0	102	101	101	100	101	100	100	99	99	99	98	98	98	97	97	95	
Hm	0.34Hm	0.34Hm	5.0	102	102	101	101	101	101	100	100	99	99	99	98	98	97	97	95	
			7.0	103	102	102	102	102	101	101	100	100	100	99	98	98	98	98	96	
			10.0	103	103	103	103	102	102	102	102	100	100	100	98	98	98	98	96	

