

屋内照明器具特性

品番 (品名)	NTN82430	
光源	LDR3L-W-E11 ×1	365.0 1m
管理番号	K0174895(3)DR1	
BZ分類	BZ1	

器具効率	95%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	95%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	83	78	75	73	82	78	75	73	81	77	74	72	80	77	74	72	71	
	中 0.63		88	84	81	79	87	83	81	78	86	83	80	78	85	82	80	78	77	
	否 0.56		91	87	84	82	90	87	84	82	89	86	84	82	88	85	83	81	80	
下方投影面積 等価発光面積	cm ²	1.25	94	90	88	86	93	90	87	85	91	89	87	85	90	88	86	84	83	
		1.5	95	92	90	88	94	92	89	88	93	90	89	87	91	89	88	86	85	
取付高さ	器具間隔最大限		2.5	98	96	95	93	97	96	94	93	96	94	93	92	94	93	92	91	89
	横方向 (A)	縦方向 (B)	3.0	99	97	96	94	98	97	95	94	96	95	94	93	95	94	93	92	90
Hm	0.59Hm	0.60Hm	4.0	100	99	97	96	99	98	97	96	97	96	95	94	95	95	94	93	91
			5.0	101	100	99	98	100	99	98	97	98	97	96	95	96	95	95	94	92
			7.0	101	100	100	99	100	100	99	98	98	98	97	97	96	96	95	95	93
			10.0	102	101	101	100	101	100	99	99	98	98	97	97	96	96	96	93	

