

屋内照明器具特性	
品番 (品名)	NTN88007W
光源	LLD4000LCB1 ×1 845.0 lm
管理番号	K0179471 (0) DR 1
BZ分類	BZ4/1.1/BZ3/3.5/BZ4

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	43	34	29	26	42	34	29	26	40	33	29	26	39	33	28	25	24
			0.63	0.8	50	43	37	34	49	42	37	34	47	41	37	34	46	40	36	33	32
			0.56	1.0	55	48	43	39	54	47	43	39	52	46	42	39	50	45	42	39	37
				1.25	59	53	48	45	58	52	48	45	56	51	47	44	54	50	47	44	43
下方投影面積		cm ²		1.5	62	56	52	49	61	56	52	49	59	54	51	48	57	53	50	48	46
			等価発光面積	cm ²	2.0	65	61	57	54	64	60	57	54	62	59	56	53	60	58	55	53
取付 高さ	器具間隔最大限			2.5	68	64	61	58	67	63	60	58	65	62	59	57	63	60	58	56	55
	横方向 (A)		縦方向 (B)	3.0	69	66	63	61	68	65	63	60	66	64	61	59	64	62	60	59	57
H m	1.29 H m		1.29 H m	4.0	71	69	66	64	70	68	66	64	68	66	64	63	66	65	63	62	60
				5.0	72	70	68	66	71	69	68	66	69	68	66	65	68	66	65	64	62
				7.0	73	72	71	69	73	71	70	69	71	70	68	67	69	68	67	66	64
				10.0	74	73	72	71	74	73	72	71	72	71	70	69	70	69	69	68	66

