

屋内照明器具特性	
品番 (品名)	NTN88007W
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0181916 (0) DR 1
BZ分類	BZ4

器具効率		89 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z
保守率	良 中 否	0.67	0.6	53	42	35	31	51	42	35	31	49	41	35	30	47	40	34	30	29					
		0.63	0.8	62	52	45	41	60	51	45	40	58	50	44	40	56	49	44	40	38					
		0.56	1.0	68	59	52	48	66	58	52	47	64	57	51	47	62	55	51	47	45					
			1.25	73	65	59	54	72	64	59	54	69	63	58	54	67	61	57	53	51					
下方投影面積		cm ²	1.5	77	69	64	59	75	69	63	59	73	67	62	59	70	65	61	58	56					
等価発光面積			2.0	81	76	71	67	80	75	70	66	78	73	69	66	75	71	68	65	63					
取付	器具間隔最大限		2.5	84	79	75	72	83	78	75	71	81	77	73	70	78	75	72	69	67					
高さ	横方向 (A) 縦方向 (B)		3.0	86	82	78	75	85	81	78	75	83	79	76	74	80	77	75	73	70					
H m	1.29 H m	1.29 H m	4.0	89	86	83	80	88	85	82	79	85	83	80	78	83	81	79	77	75					
			5.0	91	88	85	83	89	87	84	82	87	85	83	81	85	83	81	80	77					
			7.0	92	90	88	86	91	89	87	86	89	87	86	84	87	85	84	83	80					
			10.0	94	92	91	89	92	91	90	88	90	89	88	87	88	87	86	85	83					

