

屋内照明器具特性	
品番 (品名)	NTN88008W
光源	LLD3020CU1 ×1 615.0 l m
管理番号	K0181919 (0) DR 1
B Z 分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M	
下方光束		88 %																					
保守率		良	0.67	0.6	73	67	64	62	72	67	64	61	71	67	64	61	70	66	63	61	60		
		中	0.63	0.8	78	73	70	67	77	73	69	67	76	72	69	67	75	71	69	67	66		
		否	0.56	1.0	81	77	74	71	80	76	73	71	79	75	73	71	78	75	72	70	69		
		0.56	1.25	84	80	77	75	83	79	77	75	82	78	76	74	80	77	75	74	72			
下方投影面積		c m ²		1.5	86	82	80	77	85	82	79	77	83	81	78	77	82	79	78	76	75		
等価発光面積		c m ²		2.0	88	85	83	81	87	85	82	81	85	83	81	80	84	82	80	79	78		
取付高さ	器具間隔最大限			2.5	90	87	85	83	89	86	85	83	87	85	83	82	85	84	82	81	79		
	横方向 (A)		縦方向 (B)	3.0	90	88	87	85	90	88	86	85	88	86	85	84	86	85	84	83	81		
H m	0.34 H m	0.34 H m	4.0	92	90	89	87	91	89	88	87	89	88	86	85	87	86	85	84	82			
			5.0	92	91	90	89	91	90	89	88	89	88	88	87	88	87	86	85	83			
			7.0	93	92	91	90	92	91	90	90	90	89	89	88	88	88	87	87	84			
			10.0	94	93	92	92	93	92	91	91	91	90	90	89	89	89	88	88	85			

