


屋外照明器具特性

品番(品名)	YYY81282																			
光源	LED4000_85_190 x1	190.0 lm																		
管理番号	K0172274(0)DB1																			
JISC8131-1999 による配光形式																				
器具効率	100.0%	直下光度	0.4 cd/1000lm																	
上方光束	3.3%	最大光度	866.4 cd/1000lm																	
下方光束	96.7%																			
鉛直角	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	
=0°鉛直面	0	0	52	185	346	515	665	775	842	853	701	487	203	116	66	48	36	26	18	
90°	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
180°	0	0	55	250	376	468	487	253	186	139	102	70	40	26	16	12	9	8	5	
270°	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
I _{max} を含む鉛直面	0	0	52	182	346	518	670	784	853	866	719	502	210	119	67	48	36	26	18	



道路・トンネル照明率曲線

品番(品名)

YYY81282

光源

LED4000_85_190 ×1


管理番号

K0172274 (0)DB 1

————— = 0.0°

H: 取付高さ

照明率(= 0°)		
幅	歩道側	車道側
0.0H	0.000	0.000
0.2H	0.000	0.001
0.4H	0.053	0.049
0.6H	0.143	0.152
0.8H	0.207	0.274
1.0H	0.237	0.387
1.2H	0.254	0.476
1.4H	0.265	0.538
1.6H	0.271	0.577
1.8H	0.275	0.601
2.0H	0.278	0.617
2.2H	0.280	0.627
2.4H	0.282	0.634
2.6H	0.283	0.640
2.8H	0.284	0.644
3.0H	0.285	0.647
3.2H	0.285	0.650
3.4H	0.286	0.652
3.6H	0.286	0.654



歩道側



車道側

正弦等光度曲線

品番(品名)	YYY81282	光源	LED4000_85_190 ×1
管理番号	K0172274(0)DB 1		

