

# 屋内照明器具特性

品番 (品名)	LRD1121V	
光源	LED3500_70_455 ×1	455.0 lm
管理番号	K0160345(0)D 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	88	83	80	77	87	83	79	77	86	82	79	77	85	81	79	77	76
	中	0.63	0.8	93	88	85	83	92	88	85	83	91	87	84	82	89	86	84	82	81
	否	0.56	1.0	96	92	89	86	95	91	88	86	93	90	88	86	92	89	87	85	84
下方投影面積	cm <sup>2</sup>	1.25	98	95	92	90	97	94	91	89	96	93	91	89	94	92	90	88	87	
		1.5	100	97	94	92	99	96	94	92	97	95	93	91	96	94	92	90	89	
等価発光面積	cm <sup>2</sup>	2.0	102	99	97	95	101	99	97	95	99	97	95	94	97	96	94	93	91	
		2.5	103	101	99	97	102	100	98	97	100	99	97	96	99	97	96	95	93	
取付高さ	器具間隔最大限		3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96	94
	横方向 (A)	縦方向 (B)	4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	98	95
Hm	0.36Hm	0.37Hm	5.0	106	105	103	102	105	104	102	102	103	102	101	100	101	100	99	99	96
			7.0	107	106	105	104	105	105	104	103	103	103	102	101	101	101	100	100	100
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98

