

# 屋内照明器具特性

品番 (品名)	NDN46590S		
光源	LED9999_70_3805 ×1	3805.0lm	
管理番号	K0170510(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	壁	10%				10%				10%				10%				0%	
下方光束	100%	床	10%				10%				10%				10%				0%	
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	88	83	80	78	88	83	80	78	87	82	80	78	86	82	79	77	77
	中	0.63	0.8	94	89	86	84	93	89	86	84	92	88	85	84	90	87	85	83	82
	否	0.56	1.0	97	93	90	88	96	92	90	88	95	91	89	87	93	91	89	87	86
下方投影面積 等価発光面積	cm <sup>2</sup>	cm <sup>2</sup>	1.25	99	96	93	91	98	95	93	91	97	94	92	90	95	93	91	90	89
			1.5	101	98	95	93	100	97	95	93	98	96	94	92	97	95	93	92	90
			2.0	103	100	98	97	102	100	98	96	100	98	97	95	98	97	96	94	93
取付高さ	器具間隔最大限		2.5	104	102	100	99	103	101	99	98	101	100	98	97	99	98	97	96	94
	横方向 (A)	縦方向 (B)	3.0	105	103	101	100	104	102	101	99	102	101	99	98	100	99	98	97	95
Hm	0.78Hm	0.78Hm	4.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	99	99	96
			5.0	106	105	104	103	105	104	103	102	103	102	101	101	101	100	99	99	97
			7.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	99	98
			10.0	108	107	106	106	106	106	105	105	104	104	103	103	102	102	101	101	99

