

屋内照明器具特性	
品番 (品名)	NTN83054
光源	LED2700_70_860 ×1 860.0 1m
管理番号	K0169805 ( 0 ) DY1
BZ分類	BZ6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 ( X0.01 ) ZCM																				
保守率		良 中 否	0.69	0.6	52	39	31	25	49	38	30	25	45	35	29	24	42	33	27	23	20				
			0.67	0.8	61	49	40	34	58	47	39	34	54	44	37	32	49	41	35	31	27				
			0.63	1.0	67	56	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33				
				1.25	73	62	54	48	70	60	53	47	65	56	50	45	60	53	47	43	38				
下方投影面積		cm <sup>2</sup>		1.5	77	67	59	53	74	65	58	52	68	61	55	50	63	57	52	47	42				
			等価発光面積	cm <sup>2</sup>	2.0	83	74	67	61	80	72	65	60	74	67	62	57	68	63	58	54	49			
取付 高さ	器具間隔最大限			2.5	86	79	73	67	83	76	71	65	77	72	67	62	72	67	63	59	54				
	横方向 ( A ) 縦方向 ( B )			3.0	89	82	77	72	86	80	74	70	80	75	70	66	74	70	66	63	57				
1.5m	2.03 m	1.96 m		4.0	92	87	82	78	89	84	80	76	83	79	75	72	78	74	71	68	62				
2	2.7	2.59		5.0	95	90	86	82	91	87	83	80	85	82	79	76	80	77	74	72	65				
2.5	3.4	3.22		7.0	97	94	90	87	94	91	88	85	88	85	83	80	83	80	78	76	69				
3	4.05	3.84		10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	81	80	73				

