

屋内照明器具特性	
品番 (品名)	NTN83090
光源	LED5000_70_510 x1 510.0 lm
管理番号	K0170346(0)DY1
BZ分類	BZ2/1.4/BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	97%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	68	58	52	48	67	58	52	48	64	56	51	47	62	55	51	47	45
	中	0.67	0.8	76	67	61	57	75	66	61	56	72	65	60	56	70	63	59	55	53
	否	0.63	1.0	81	73	67	63	80	72	67	62	77	70	66	62	74	69	65	61	59
			1.25	86	79	73	69	84	78	72	68	81	76	71	67	79	74	70	67	64
下方投影面積	c m ²		1.5	89	82	77	73	87	81	76	72	84	79	75	71	82	77	74	70	68
	等価発光面積		c m ²	2.0	93	88	83	79	92	86	82	79	88	84	80	77	86	82	79	76
取付高さ	器具間隔最大限		2.5	96	91	87	84	94	90	86	83	91	87	84	81	88	85	82	80	77
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	96	92	89	86	93	90	87	84	90	87	85	83	80
1.5m	0.93m	1.75m	4.0	100	97	94	91	98	95	93	90	95	93	90	88	92	90	88	86	83
2	1.24	2.33	5.0	101	99	96	94	100	97	95	93	97	94	93	91	94	92	90	89	85
2.5	1.55	2.92	7.0	103	101	99	97	101	100	98	96	98	97	95	94	95	94	93	92	88
3	1.86	3.5	10.0	104	103	101	100	103	101	100	99	100	98	97	96	97	96	95	94	90

