

屋内照明器具特性	
品番 (品名)	NTN83124
光源	LED2700_70_1840 x1 1840.0 lm
管理番号	K0173007(0)DY1
BZ分類	BZ2/1.1/BZ3/8.5/BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	67	57	51	47	66	57	51	47	63	55	50	46	61	54	49	46	44
	中	0.67	0.8	75	66	60	56	74	65	60	55	71	64	59	55	69	63	58	54	52
	否	0.63	1.0	81	72	66	62	79	71	66	62	76	70	65	61	74	68	64	60	58
			1.25	85	78	72	68	84	77	72	67	81	75	70	67	78	73	69	66	63
下方投影面積		cm ²	1.5	89	82	76	72	87	81	76	72	84	79	74	71	81	76	73	70	67
等価発光面積		cm ²	2.0	93	87	83	79	91	86	82	78	88	84	80	77	85	81	78	75	73
取付高さ	器具間隔最大限		2.5	96	91	87	83	94	89	86	82	91	87	84	81	88	85	82	79	76
	横方向 (A)	縦方向 (B)	3.0	97	93	89	86	96	92	88	85	93	89	86	84	89	87	84	82	79
1.5m	1m	1.98m	4.0	100	96	93	91	98	95	92	90	95	92	90	88	92	90	88	86	83
2	1.34	2.5	5.0	101	98	96	93	100	97	95	92	96	94	92	90	93	92	90	88	85
2.5	1.67	3.04	7.0	103	101	99	97	101	99	98	96	98	96	95	93	95	94	92	91	88
3	2	3.59	10.0	104	103	101	100	103	101	100	98	99	98	97	96	96	96	95	94	90

