

# 屋内照明器具特性

品番 (品名)	LRD9 2 0 2	
光源	LLD4000LCB1 ×1	845.0 lm
管理番号	K0175982 ( 0 ) DR 1	
BZ分類	BZ3	

器具効率	50%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		50%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	31	26	22	20	31	26	22	20	30	25	22	20	29	25	22	20	19	
	中	0.6	0.8	37	32	28	26	36	31	28	26	35	31	28	26	34	30	27	25	24	
	否	0.56	1.0	40	35	32	30	39	35	32	30	38	34	32	30	37	34	31	29	28	
			1.25	43	39	36	34	42	38	36	33	41	38	35	33	40	37	35	33	32	
下方投影面積	c m <sup>2</sup>		1.5	45	41	38	36	44	41	38	36	43	40	38	36	41	39	37	35	34	
	等価発光面積		c m <sup>2</sup>	2.0	47	44	42	40	46	44	42	40	45	43	41	39	44	42	40	39	38
取付高さ	器具間隔最大限		2.5	49	46	44	42	48	46	44	42	47	45	43	42	45	44	42	41	40	
	横方向 (A)	縦方向 (B)	3.0	50	47	46	44	49	47	45	44	48	46	45	43	46	45	44	43	42	
H m	1.21 H m	1.21 H m	4.0	51	49	48	46	50	49	47	46	49	48	46	45	48	47	46	45	44	
			5.0	51	50	49	48	51	50	49	48	50	49	48	47	48	48	47	46	45	
			7.0	52	51	50	50	52	51	50	49	50	50	49	48	49	49	48	48	46	
			10.0	53	52	52	51	52	52	51	50	51	51	50	50	50	50	49	49	47	

