

# 屋内照明器具特性

品番 (品名)	NTN83420									
光源	LED5000_70_550 x1					550.0 lm				
管理番号	K0167959(0)DY1									
BZ分類	BZ7/0.7/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%			
	上方光束		27%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		73%		床	10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM		
保守率	良	0.69	0.6	4.9	3.6	2.8	2.2	4.6	3.4	2.6	2.1	4.1	3.1	2.4	2.0	3.6	2.8	2.2	1.8	1.4		
	中	0.67	0.8	5.8	4.5	3.7	3.0	5.4	4.3	3.5	2.9	4.8	3.9	3.2	2.7	4.3	3.5	2.9	2.5	2.0		
	否	0.63	1.0	6.4	5.2	4.3	3.7	6.0	4.9	4.1	3.5	5.4	4.5	3.8	3.3	4.8	4.0	3.5	3.0	2.5		
			1.25	6.9	5.8	5.0	4.4	6.6	5.6	4.8	4.2	5.9	5.0	4.4	3.9	5.2	4.5	4.0	3.6	3.0		
下方投影面積			c m <sup>2</sup>		1.5	7.4	6.3	5.5	4.9	7.0	6.0	5.3	4.7	6.2	5.5	4.9	4.3	5.5	4.9	4.4	4.0	3.3
			c m <sup>2</sup>		2.0	7.9	7.0	6.3	5.7	7.5	6.7	6.0	5.5	6.7	6.1	5.5	5.1	6.0	5.5	5.0	4.7	3.9
取付高さ	器具間隔最大限				2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.6	6.0	7.1	6.5	6.0	5.6	6.4	5.9	5.5	5.1	4.3
	横方向 (A)	縦方向 (B)			3.0	8.6	7.9	7.3	6.7	8.2	7.5	7.0	6.5	7.3	6.8	6.4	6.0	6.6	6.2	5.8	5.5	4.7
1.5m	2.49m	1.98m			4.0	8.9	8.3	7.8	7.4	8.5	8.0	7.5	7.1	7.7	7.3	6.9	6.5	6.9	6.6	6.3	6.0	5.1
2	3.31	2.6			5.0	9.1	8.7	8.2	7.8	8.7	8.3	7.9	7.5	7.9	7.5	7.2	6.9	7.1	6.9	6.6	6.3	5.4
2.5	4.19	3.23			7.0	9.4	9.0	8.7	8.3	9.0	8.6	8.3	8.0	8.2	7.9	7.6	7.4	7.4	7.2	7.0	6.8	5.8
3	5.02	3.86			10.0	9.6	9.3	9.1	8.8	9.2	8.9	8.7	8.5	8.4	8.2	8.0	7.8	7.6	7.5	7.3	7.1	6.2

