

屋内照明器具特性

品番 (品名)	NTN83494															
光源	LED2700_70_1160 x1 1160.0 1m															
管理番号	K0167960(0)DY1															
BZ分類	BZ7/0.7/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	27%	室指数																			
下方光束	73%	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.69	0.6	4.9	3.6	2.8	2.2	4.6	3.4	2.6	2.1	4.1	3.1	2.4	2.0	3.6	2.8	2.2	1.8	1.4	
		0.67	0.8	5.8	4.5	3.7	3.0	5.4	4.3	3.5	2.9	4.8	3.9	3.2	2.7	4.3	3.5	2.9	2.5	2.0	
			1.0	6.4	5.2	4.3	3.7	6.0	4.9	4.1	3.5	5.4	4.5	3.8	3.3	4.7	4.0	3.5	3.0	2.5	
		0.63	1.25	6.9	5.8	5.0	4.4	6.6	5.6	4.8	4.2	5.9	5.0	4.4	3.9	5.2	4.5	4.0	3.6	3.0	
下方投影面積	c m ²	1.5	7.4	6.3	5.5	4.9	7.0	6.0	5.3	4.7	6.2	5.5	4.8	4.3	5.5	4.9	4.4	4.0	3.3		
		2.0	7.9	7.0	6.3	5.7	7.5	6.7	6.0	5.5	6.7	6.1	5.5	5.1	6.0	5.5	5.0	4.6	3.9		
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.6	6.0	7.1	6.5	6.0	5.6	6.3	5.9	5.5	5.1	4.3	
	横方向 (A)	縦方向 (B)	3.0	8.6	7.9	7.3	6.7	8.1	7.5	7.0	6.5	7.3	6.8	6.4	6.0	6.6	6.2	5.8	5.5	4.6	
1.5m	2.55m	2.29m	4.0	8.9	8.3	7.8	7.4	8.5	8.0	7.5	7.1	7.7	7.3	6.9	6.5	6.9	6.6	6.3	6.0	5.1	
2	3.35	2.84	5.0	9.1	8.6	8.2	7.8	8.7	8.3	7.9	7.5	7.9	7.5	7.2	6.9	7.1	6.8	6.6	6.3	5.4	
2.5	4.17	3.43	7.0	9.4	9.0	8.7	8.3	9.0	8.6	8.3	8.0	8.2	7.9	7.6	7.4	7.4	7.2	7.0	6.8	5.8	
3	4.99	4.02	10.0	9.6	9.3	9.1	8.8	9.2	8.9	8.7	8.4	8.4	8.2	8.0	7.8	7.6	7.5	7.3	7.1	6.2	

