

屋内照明器具特性

品番 (品名)	NTN83264															
光源	LED2700_70_50 x1 50.0 lm															
管理番号	K0167962(0)DY1															
BZ分類	BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	16%	床	10%				10%				10%				10%				0%	
下方光束	84%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.69	0.6	51	39	31	25	49	38	30	25	45	35	28	24	42	33	27	23	19
	中	0.67	0.8	61	48	40	34	58	47	39	33	53	44	37	32	49	41	35	31	27
	否	0.63	1.0	67	55	47	41	64	54	46	40	59	50	43	38	54	47	41	36	32
			1.25	73	62	54	48	70	60	53	47	64	56	50	45	59	52	47	43	38
下方投影面積	c m ²		1.5	77	67	59	53	74	65	58	52	68	61	54	49	63	57	51	47	42
等価発光面積	c m ²		2.0	83	74	67	61	79	72	65	60	74	67	62	57	68	63	58	54	49
取付高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	71	66	62	71	67	63	59	53
	横方向 (A)	縦方向 (B)	3.0	89	82	76	71	86	80	74	70	80	75	70	66	74	70	66	63	57
H m	1.43 H m	1.23 H m	4.0	92	87	82	78	89	84	80	76	83	79	75	72	77	74	71	68	62
			5.0	94	90	86	82	91	87	83	80	85	82	79	76	80	77	74	72	65
			7.0	97	93	90	87	94	91	88	85	88	85	83	80	82	80	78	76	69
			10.0	99	96	94	91	96	94	91	89	90	88	86	84	84	83	81	80	73

