

屋内照明器具特性

品番 (品名)	LSEB7108				
光源	LED5000_70_840	x1	840.0	1m	
管理番号	K0140471(0)DB1				
BZ分類	BZ6/0.7/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 17%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	83%	床		10%				10%				10%				10%				0%			
室指数	照明率 (X0.01)																				ZCM		
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6			
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6			
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56			
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56			
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0			
	等価発光面積		c m ²																				
取付高さ	器具間隔最大限																						
	横方向 (A)	縦方向 (B)																					
1.5m	2.12m	1.86m	4.0	9.3	8.8	8.3	7.9	9.0	8.5	8.1	7.7	8.4	8.0	7.6	7.3	7.8	7.5	7.2	6.9	6.3			
2	2.84	2.47	5.0	9.5	9.1	8.7	8.3	9.2	8.8	8.4	8.1	8.6	8.2	8.0	7.7	8.0	7.7	7.5	7.3	6.6			
2.5	3.53	3.08	7.0	9.7	9.4	9.1	8.8	9.4	9.1	8.9	8.6	8.8	8.6	8.3	8.1	8.2	8.0	7.8	7.7	7.0			
3	4.24	3.69	10.0	9.9	9.7	9.5	9.2	9.6	9.4	9.2	9.0	9.0	8.8	8.7	8.5	8.4	8.3	8.1	8.0	7.3			

