

屋内照明器具特性

品番 (品名)	XLX408GENJ										
光源	LED5000_85_8980 x1 8980.0 lm										
管理番号	K0146093(3)DB1										
BZ分類	BZ5/0.7/BZ4										

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	58	46	38	33	56	45	38	33	54	44	37	33	52	43	37	32	31
	中	0.77	0.8	68	57	49	44	67	56	49	44	64	55	49	44	62	54	48	43	41
	否	0.68	1.0	75	65	58	52	74	64	57	52	71	62	56	51	68	61	56	51	49
			1.25	81	72	65	60	80	71	65	60	77	69	64	59	74	68	63	59	56
下方投影面積		cm ²	1.5	85	77	71	65	84	76	70	65	81	74	69	65	78	72	68	64	62
等価発光面積		cm ²	2.0	91	84	78	74	89	83	78	73	86	81	76	72	83	79	75	72	69
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	83	79	90	85	81	78	87	83	80	77	74
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	83	92	88	85	82	89	86	83	80	78
1.5m	2.09m	2.16m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	92	90	88	85	83
2	2.77	2.72	5.0	101	98	95	92	100	97	94	91	97	94	92	90	94	92	90	88	86
2.5	3.44	3.31	7.0	103	101	98	96	102	99	97	95	99	97	95	94	97	95	94	92	89
3	4.11	3.91	10.0	104	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92

