

屋内照明器具特性

品番 (品名)	XLX400FEVJ									
光源	LED3500_85_8780 x1					8780.0 lm				
管理番号	K0132392(1)DB1									
BZ分類	BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.81	0.6	59	47	40	35	58	47	40	35	55	46	39	34	53	45	39	34	32	
	中	0.77	0.8	70	59	51	46	68	58	51	46	66	57	50	46	63	55	50	45	43	
	否	0.68	1.0	76	66	59	54	75	66	59	54	72	64	58	54	70	63	57	53	51	
			0.68	1.25	82	73	67	62	81	73	66	61	78	71	65	61	75	69	64	60	58
下方投影面積			1.5	86	78	72	67	85	77	71	67	82	75	70	66	79	74	69	66	63	
			2.0	91	85	80	75	90	84	79	75	87	82	78	74	84	80	76	73	71	
取付高さ	器具間隔最大限		2.5	95	89	84	80	93	88	84	80	90	86	82	79	88	84	81	78	76	
	横方向 (A)	縦方向 (B)	3.0	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	82	79	
1.5m	2.03m	2.18m	4.0	100	96	92	89	98	95	92	89	95	93	90	87	93	91	88	86	84	
2	2.68	2.74	5.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	89	86	
2.5	3.33	3.34	7.0	103	101	99	97	102	100	98	96	99	98	96	94	97	95	94	93	90	
3	3.98	3.94	10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	97	96	95	93	

