

屋内照明器具特性

品番 (品名)	XLX400DEV C									
光源	LED3500_85_9530 x1 9530.0 1m									
管理番号	K0159374(0)D 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	96 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.83 中 0.81 否 0.77	0.6	55	43	35	29	54	42	34	29	51	41	34	29	48	39	33	28	26	
		0.8	65	53	45	39	63	52	45	39	60	50	44	38	57	49	43	38	35	
		1.0	71	60	52	46	70	59	52	46	66	57	50	45	63	55	49	45	42	
		1.25	77	67	60	54	75	66	59	53	72	64	57	52	68	61	56	51	48	
下方投影面積	c m ²	1.5	81	72	65	59	79	71	64	59	76	68	62	57	72	66	61	56	53	
		2.0	87	79	73	67	85	78	72	67	81	75	70	65	77	72	68	64	61	
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	82	77	72	85	79	75	71	81	77	73	69	66
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	86	81	76	87	83	78	75	84	80	76	73	70
1.5m	1.98 m	2.13 m	4.0	96	91	87	83	94	90	86	82	91	87	83	80	87	84	81	78	75
2	2.61	2.67	5.0	98	94	91	87	96	93	89	86	93	90	87	84	89	87	84	82	78
2.5	3.25	3.23	7.0	101	98	95	92	99	96	93	91	95	93	91	88	92	90	88	86	82
3	3.88	3.82	10.0	103	100	98	96	101	99	97	95	97	95	94	92	94	92	91	90	86

