

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | NYY56259K+NTS90200 |  |  |  |  |           |  |  |  |  |
| 光源      | LED5000_85_1660 x1 |  |  |  |  | 1660.0 lm |  |  |  |  |
| 管理番号    | K0149444(0)DB1     |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ1                |  |  |  |  |           |  |  |  |  |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0%  |    |
|        |         | 壁               | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0%  |    |
| 上方光束   | 0%      | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0%  |    |
| 下方光束   | 100%    | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |    |
| 保守率    | 良       | 0.81            | 0.6           | 74  | 66  | 60  | 57  | 73  | 65  | 60  | 57  | 71  | 65  | 60  | 57  | 70  | 64  | 60 | 56  | 55 |
|        | 中       | 0.77            | 0.8           | 82  | 75  | 70  | 67  | 81  | 75  | 70  | 66  | 80  | 74  | 69  | 66  | 78  | 73  | 69 | 66  | 64 |
|        | 否       | 0.68            | 1.0           | 88  | 81  | 77  | 73  | 87  | 81  | 76  | 73  | 85  | 79  | 75  | 72  | 83  | 78  | 75 | 72  | 71 |
|        |         |                 | 1.25          | 92  | 86  | 82  | 79  | 91  | 86  | 82  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80 | 77  | 76 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 95  | 90  | 86  | 83  | 93  | 89  | 85  | 82  | 91  | 87  | 84  | 82  | 89  | 86  | 83 | 81  | 79 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 92  | 89  | 87  | 93  | 90  | 88 | 86  | 84 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91 | 89  | 87 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 93 | 91  | 89 |
| Hm     | 1.21Hm  | 1.21Hm          | 4.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 97  | 95  | 98  | 96  | 95 | 94  | 91 |
|        |         |                 | 5.0           | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 96 | 95  | 93 |
|        |         |                 | 7.0           | 105 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98 | 97  | 95 |
|        |         |                 | 10.0          | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 99  | 96 |

