

屋内照明器具特性

| | | |
|---------|-----------------|----------|
| 品番 (品名) | LGB15377 | |
| 光源 | LLD3020MLCE1 ×1 | 795.0 lm |
| 管理番号 | K0176242(0)DR1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 63% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 | | 0% | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 63% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 51 | 47 | 45 | 43 | 51 | 47 | 45 | 43 | 50 | 47 | 45 | 43 | 49 | 46 | 44 | 43 | 42 |
| | 中 | 0.63 | 0.8 | 55 | 52 | 49 | 47 | 55 | 51 | 49 | 47 | 54 | 51 | 49 | 47 | 53 | 50 | 48 | 47 | 46 |
| | 否 | 0.56 | 1.0 | 58 | 54 | 52 | 50 | 57 | 54 | 52 | 50 | 56 | 53 | 51 | 50 | 55 | 53 | 51 | 49 | 49 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 60 | 57 | 54 | 53 | 59 | 56 | 54 | 52 | 58 | 55 | 54 | 52 | 57 | 55 | 53 | 52 | 51 |
| | | | 1.5 | 61 | 58 | 56 | 54 | 60 | 58 | 56 | 54 | 59 | 57 | 55 | 54 | 58 | 56 | 55 | 53 | 52 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 63 | 60 | 59 | 57 | 62 | 60 | 58 | 57 | 61 | 59 | 58 | 56 | 59 | 58 | 57 | 56 | 55 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 64 | 62 | 60 | 59 | 63 | 61 | 60 | 59 | 62 | 60 | 59 | 58 | 60 | 59 | 58 | 57 | 56 |
| Hm | 0.47Hm | 0.47Hm | 3.0 | 64 | 63 | 61 | 60 | 64 | 62 | 61 | 60 | 62 | 61 | 60 | 59 | 61 | 60 | 59 | 58 | 57 |
| | | | 4.0 | 65 | 64 | 63 | 62 | 65 | 63 | 62 | 61 | 63 | 62 | 61 | 61 | 62 | 61 | 60 | 60 | 58 |
| | | | 5.0 | 66 | 65 | 64 | 63 | 65 | 64 | 63 | 62 | 64 | 63 | 62 | 62 | 62 | 61 | 61 | 59 | 59 |
| | | | 7.0 | 66 | 66 | 65 | 64 | 66 | 65 | 64 | 64 | 64 | 64 | 63 | 63 | 63 | 63 | 62 | 62 | 60 |
| | | | 10.0 | 67 | 66 | 66 | 65 | 66 | 66 | 65 | 65 | 65 | 64 | 64 | 64 | 63 | 63 | 63 | 62 | 61 |

