

屋内照明器具特性	
品番 (品名)	LGB15106
光源	LLD4000MLCB1 ×1 845.0 l m
管理番号	K0176195 (0) DR 1
BZ分類	BZ5

器具効率	60 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	3 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	57 %																																																						
保守率	良 中 否	0.67	0.6	33	26	21	18	32	25	21	18	30	24	20	17	29	23	20	17	16																																			
		0.63	0.8	39	32	27	24	38	31	27	23	36	30	26	23	34	29	26	23	21																																			
			1.0	43	36	32	28	42	36	31	28	40	34	30	27	38	33	30	27	25																																			
		0.56	1.25	47	41	36	33	45	40	36	32	43	38	35	32	41	37	34	31	29																																			
下方投影面積	c m ²	1.5	49	44	39	36	48	43	39	36	45	41	38	35	43	40	37	34	32																																				
		2.0	53	48	44	41	51	47	43	41	49	45	42	40	47	44	41	39	37																																				
取付高さ	器具間隔最大限		2.5	55	51	47	45	53	50	47	44	51	48	45	43	49	46	44	42																																				
	横方向 (A)	縦方向 (B)	3.0	56	53	50	47	55	52	49	47	53	50	48	45	50	48	46	44																																				
H m	1.16 H m	1.16 H m	4.0	58	55	53	51	57	54	52	50	55	52	51	49	52	51	49	47																																				
			5.0	59	57	55	53	58	56	54	52	56	54	52	51	54	52	51	50																																				
			7.0	61	59	57	56	60	58	57	55	57	56	55	54	55	54	53	52																																				
			10.0	62	61	59	58	61	60	58	57	58	57	57	56	56	55	54	51																																				

