

屋内照明器具特性

品番 (品名) **LGB16736**

光源 **LLD3020MLCE1 ×1** **795.0 lm**

管理番号 **K0176197(0)DR1**

BZ分類 **BZ1**

器具効率	73%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	72%	床		10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	57	52	48	46	56	51	48	46	55	51	48	46	54	50	47	45	44	
	中 0.63	0.8	62	57	54	51	61	56	53	51	60	56	53	51	58	55	52	50	49	
	否 0.56	1.0	65	60	57	55	64	60	57	55	62	59	56	54	61	58	56	54	53	
下方投影面積	cm ²	1.25	67	63	60	58	66	63	60	58	65	62	59	57	63	61	59	57	56	
		1.5	69	66	63	61	68	65	62	60	66	64	61	60	65	63	61	59	58	
等価発光面積	cm ²	2.0	71	68	66	64	70	68	65	64	69	66	64	63	67	65	64	62	61	
		2.5	73	70	68	66	72	69	68	66	70	68	66	65	68	67	65	64	62	
取付高さ	器具間隔最大限		3.0	74	72	70	68	73	71	69	67	71	69	68	66	69	68	67	65	64
Hm	横方向 (A)	縦方向 (B)	4.0	75	73	72	70	74	72	71	70	72	71	70	69	70	69	68	67	65
	0.48Hm	0.48Hm	5.0	76	74	73	72	75	73	72	71	73	72	71	70	71	70	69	69	67
			7.0	77	75	74	74	76	75	74	73	74	73	72	71	72	71	71	70	68
			10.0	77	76	76	75	76	75	75	74	74	74	73	73	72	72	72	71	69

