

屋内照明器具特性	
品番 (品名)	LGB16736
光源	LLD4000LCB1 ×1 845.0 lm
管理番号	K0176188(0)DR1
BZ分類	BZ5

器具効率	64%	天井	80%				70%				50%				30%				0%		
	上方光束		3%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		61%		床	10%				10%				10%				10%			
室指数	照明率 (×0.01)																			ZCM	
保守率	良	0.67	0.6	3.5	2.7	2.2	1.9	3.4	2.7	2.2	1.8	3.2	2.6	2.1	1.8	3.0	2.5	2.1	1.8	1.6	
	中	0.63	0.8	4.1	3.4	2.9	2.5	4.0	3.3	2.8	2.5	3.8	3.2	2.8	2.4	3.6	3.1	2.7	2.4	2.2	
	否	0.56	1.0	4.5	3.8	3.3	3.0	4.4	3.8	3.3	2.9	4.2	3.6	3.2	2.9	4.0	3.5	3.1	2.8	2.6	
	下方投影面積	c㎡		1.25	4.9	4.3	3.8	3.4	4.8	4.2	3.8	3.4	4.5	4.0	3.6	3.3	4.3	3.9	3.5	3.3	3.1
等価発光面積	c㎡		1.5	5.2	4.6	4.2	3.8	5.1	4.5	4.1	3.7	4.8	4.3	4.0	3.7	4.6	4.2	3.9	3.6	3.4	
	c㎡		2.0	5.6	5.1	4.7	4.3	5.4	5.0	4.6	4.3	5.2	4.8	4.5	4.2	4.9	4.6	4.3	4.1	3.9	
取付高さ	器具間隔最大限		2.5	5.8	5.4	5.0	4.7	5.7	5.3	4.9	4.6	5.4	5.1	4.8	4.5	5.2	4.9	4.6	4.4	4.2	
	横方向 (A)	縦方向 (B)	3.0	6.0	5.6	5.3	5.0	5.8	5.5	5.2	4.9	5.6	5.3	5.0	4.8	5.3	5.1	4.9	4.7	4.4	
Hm	1.17Hm	1.17Hm	4.0	6.2	5.9	5.6	5.4	6.0	5.8	5.5	5.3	5.8	5.5	5.3	5.2	5.5	5.4	5.2	5.0	4.8	
			5.0	6.3	6.0	5.8	5.6	6.2	5.9	5.7	5.5	5.9	5.7	5.5	5.4	5.7	5.5	5.4	5.2	5.0	
			7.0	6.4	6.2	6.1	5.9	6.3	6.1	6.0	5.8	6.1	5.9	5.8	5.7	5.8	5.7	5.6	5.5	5.2	
			10.0	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.1	6.0	5.9	6.0	5.9	5.8	5.7	5.4	

