

屋内照明器具特性

品番 (品名) **LGB16736**

光源 **LLD2020MLCE1 ×1** **460.0 lm**

管理番号 **K0176216 (0) DR1**

BZ分類 **BZ1**

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	87 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	68	62	58	55	68	62	58	55	66	61	57	55	65	60	57	55	54	
	中 0.63	0.8	74	68	64	61	73	68	64	61	72	67	64	61	70	66	63	61	60	
	否 0.56	1.0	78	72	69	66	77	72	68	66	75	71	68	65	73	70	67	65	64	
下方投影面積	cm ²	1.25	81	76	72	70	80	75	72	69	78	74	71	69	76	73	71	69	67	
		1.5	83	79	75	73	82	78	75	72	80	77	74	72	78	75	73	71	70	
等価発光面積	cm ²	2.0	86	82	79	77	85	81	79	76	83	80	78	76	81	79	77	75	73	
		2.5	87	84	82	80	86	83	81	79	84	82	80	78	82	80	79	77	76	
取付高さ	器具間隔最大限		3.0	88	86	84	82	87	85	83	81	85	83	82	80	83	82	80	79	77
	横方向 (A)	縦方向 (B)	4.0	90	88	86	84	89	87	85	84	87	85	84	83	85	84	82	81	79
Hm	0.50Hm	0.50Hm	5.0	91	89	87	86	90	88	87	85	88	86	85	84	86	85	84	83	81
			7.0	92	90	89	88	91	89	88	87	89	88	87	86	87	86	85	85	82
			10.0	92	91	91	90	91	91	90	89	89	89	88	87	87	87	86	86	83

