

屋内照明器具特性

品番 (品名) **LGB16736**

光源 **LLD2020CU1 ×1** **468.0 lm**

管理番号 **K0179031(0)DR1**

BZ分類 **BZ1/4.5/BZ2**

器具効率	86%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	1%	反射率	壁	10%				10%				10%				10%				0%
下方光束	85%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	67	61	57	54	66	61	57	54	65	60	57	54	64	59	56	54	53
	中	0.63	0.8	73	67	63	60	72	66	63	60	70	66	62	60	69	65	62	60	58
	否	0.56	1.0	76	71	67	64	75	70	67	64	73	69	66	64	72	68	65	63	62
下方投影面積	等価発光面積	cm ²	1.25	79	74	71	68	78	74	70	68	76	72	70	67	74	71	69	67	65
			1.5	81	77	73	71	80	76	73	71	78	75	72	70	76	73	71	69	68
取付高さ	器具間隔最大限		2.5	85	82	80	77	84	81	79	77	82	80	78	76	80	78	77	75	73
	横方向 (A)	縦方向 (B)	3.0	86	84	81	79	85	83	81	79	83	81	79	78	81	80	78	77	75
H _m	0.40H _m	0.40H _m	4.0	88	86	84	82	87	85	83	81	85	83	81	80	83	81	80	79	77
			5.0	89	87	85	84	88	86	84	83	85	84	83	82	83	82	81	80	78
			7.0	90	88	87	86	89	87	86	85	86	85	84	84	84	84	83	82	80
			10.0	90	89	89	88	89	88	88	87	87	86	86	85	85	85	84	83	81

