

# 屋内照明器具特性

品番 (品名)	LGB16736				
光源	LLD40402CQ1 (KAKUSAN) ×1		860.0 1m		
管理番号	K0184422 (0) DR1				
BZ分類	BZ5				

器具効率	69 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	4 %	室指数																	照明率 ( X0.01 )																	ZCM																
下方光束	65 %																																																			
保守率	良 中 否	0.67	0.6	3.8	3.0	2.4	2.1	3.7	2.9	2.4	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	2.0	1.8																																
		0.63	0.8	4.5	3.7	3.1	2.7	4.3	3.6	3.1	2.7	4.1	3.5	3.0	2.7	3.9	3.4	2.9	2.6	2.5																																
			1.0	4.9	4.2	3.6	3.2	4.8	4.1	3.6	3.2	4.5	3.9	3.5	3.1	4.3	3.8	3.4	3.1	2.9																																
		0.56	1.25	5.3	4.6	4.1	3.7	5.2	4.6	4.1	3.7	4.9	4.4	4.0	3.6	4.7	4.2	3.9	3.6	3.4																																
下方投影面積	c m <sup>2</sup>	1.5	5.6	5.0	4.5	4.1	5.5	4.9	4.4	4.1	5.2	4.7	4.3	4.0	4.9	4.5	4.2	3.9	3.7																																	
		2.0	6.0	5.5	5.0	4.7	5.8	5.4	5.0	4.6	5.6	5.2	4.8	4.5	5.3	5.0	4.7	4.4	4.2																																	
取付高さ	器具間隔最大限		2.5	6.2	5.8	5.4	5.1	6.1	5.7	5.3	5.0	5.8	5.5	5.2	4.9	5.6	5.3	5.0	4.8	4.5																																
	横方向 (A)	縦方向 (B)	3.0	6.4	6.0	5.7	5.4	6.3	5.9	5.6	5.3	6.0	5.7	5.4	5.2	5.7	5.5	5.2	5.0	4.8																																
H m	1.13 H m	1.13 H m	4.0	6.6	6.3	6.0	5.8	6.5	6.2	5.9	5.7	6.2	6.0	5.7	5.5	6.0	5.8	5.6	5.4	5.1																																
			5.0	6.7	6.5	6.2	6.0	6.6	6.4	6.1	5.9	6.3	6.1	6.0	5.8	6.1	5.9	5.8	5.6	5.4	5.1																															
			7.0	6.9	6.7	6.5	6.3	6.8	6.6	6.4	6.2	6.5	6.4	6.2	6.1	6.3	6.1	6.0	5.9	5.6																																
			10.0	7.0	6.9	6.7	6.6	6.9	6.8	6.6	6.5	6.6	6.5	6.4	6.3	6.4	6.3	6.2	6.1	5.8																																

