

屋内照明器具特性

品番 (品名)	LGB16737	
光源	LLD2000LCE1 ×1	531.0 lm
管理番号	K0176231(0)DR1	
BZ分類	BZ5	

器具効率	62%	天井	80%				70%				50%				30%				0%		
	上方光束		2%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		60%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	3.5	2.8	2.3	2.0	3.4	2.7	2.3	2.0	3.3	2.7	2.3	2.0	3.1	2.6	2.2	1.9	1.8	
	中	0.63	0.8	4.1	3.4	3.0	2.6	4.0	3.4	2.9	2.6	3.8	3.3	2.9	2.6	3.7	3.2	2.8	2.5	2.4	
	否	0.56	1.0	4.5	3.9	3.4	3.1	4.4	3.8	3.4	3.0	4.2	3.7	3.3	3.0	4.0	3.6	3.2	3.0	2.8	
			0.56	1.25	4.9	4.3	3.9	3.5	4.8	4.2	3.8	3.5	4.6	4.1	3.7	3.4	4.4	4.0	3.6	3.4	3.2
下方投影面積 等価発光面積	cm ²		1.5	5.2	4.6	4.2	3.9	5.0	4.5	4.1	3.8	4.8	4.4	4.0	3.8	4.6	4.2	3.9	3.7	3.5	
	cm ²		2.0	5.5	5.0	4.7	4.4	5.4	5.0	4.6	4.3	5.1	4.8	4.5	4.2	4.9	4.6	4.4	4.2	4.0	
	cm ²		2.5	5.7	5.3	5.0	4.7	5.6	5.2	4.9	4.7	5.4	5.1	4.8	4.6	5.2	4.9	4.7	4.5	4.3	
取付高さ	器具間隔最大限		Hm	横方向 (A)		縦方向 (B)		Hm	Hm	Hm	Hm	Hm	Hm	Hm	Hm	Hm	Hm	Hm	Hm	Hm	
	0.82	0.82																			
			4.0	6.1	5.8	5.5	5.3	5.9	5.7	5.5	5.3	5.7	5.5	5.3	5.1	5.5	5.3	5.2	5.0	4.8	
			5.0	6.2	5.9	5.7	5.6	6.1	5.8	5.7	5.5	5.8	5.7	5.5	5.4	5.6	5.5	5.4	5.2	5.0	
			7.0	6.3	6.1	6.0	5.8	6.2	6.0	5.9	5.8	6.0	5.9	5.7	5.6	5.8	5.7	5.6	5.5	5.2	
			10.0	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	5.9	5.8	5.9	5.8	5.7	5.7	5.4	

