

屋内照明器具特性

品番 (品名) **LGB16737**

光源 **LLD2020MLCE1 ×1** **460.0 lm**

管理番号 **K0176244 (0) DR1**

BZ分類 **BZ1**

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	82 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	67	62	58	56	66	61	58	56	65	61	58	56	64	60	58	56	55
	中	0.63	0.8	72	67	64	61	71	67	63	61	70	66	63	61	68	65	63	61	60
	否	0.56	1.0	75	70	67	65	74	70	67	65	73	69	66	64	71	68	66	64	63
下方投影面積	c m ²	1.25	77	73	70	68	76	73	70	68	75	72	70	68	74	71	69	67	66	
		1.5	79	76	73	71	78	75	72	70	77	74	72	70	75	73	71	69	68	
等価発光面積	c m ²	2.0	81	78	76	74	80	78	76	74	79	77	75	73	77	75	74	72	71	
		2.5	83	80	78	76	82	80	78	76	80	78	77	75	78	77	76	74	73	
取付高さ	器具間隔最大限		3.0	84	81	80	78	83	81	79	78	81	79	78	77	79	78	77	76	74
H m	0.47 H m	0.47 H m	4.0	85	83	82	80	84	82	81	80	82	81	80	79	80	79	78	78	76
			5.0	85	84	83	82	85	83	82	81	83	82	81	80	81	80	79	79	77
			7.0	86	85	84	83	85	84	84	83	83	83	82	81	82	81	81	80	78
			10.0	87	86	85	85	86	85	85	84	84	84	83	83	82	82	81	81	79

