

屋内照明器具特性

品番 (品名) **LGB16737**

光源 **LLD3020CU1 ×1** **615.0 lm**

管理番号 **K0178729 (0) DR1**

BZ分類 **BZ1**

器具効率	54%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	54%		床	10%				10%				10%				10%				0%
		室指数	照明率 (×0.01)																ZCM	
保守率	良 0.67	0.6	44	40	38	36	43	40	38	36	42	39	38	36	42	39	37	36	35	
	中 0.63	0.8	47	44	41	40	46	43	41	40	45	43	41	40	45	42	41	39	39	
	否 0.56	1.0	49	46	44	42	48	46	44	42	47	45	43	42	46	44	43	42	41	
下方投影面積	cm ²	1.25	51	48	46	44	50	48	46	44	49	47	45	44	48	46	45	44	43	
		1.5	52	49	48	46	51	49	47	46	50	48	47	46	49	48	46	45	44	
等価発光面積	cm ²	2.0	53	51	50	48	53	51	49	48	51	50	49	48	50	49	48	47	46	
		2.5	54	52	51	50	54	52	51	50	52	51	50	49	51	50	49	49	47	
取付高さ	器具間隔最大限		3.0	55	53	52	51	54	53	52	51	53	52	51	50	52	51	50	49	48
	横方向 (A)	縦方向 (B)		4.0	56	54	53	53	55	54	53	52	54	53	52	51	53	52	51	51
H _m	0.45H _m	0.45H _m	5.0	56	55	54	54	55	55	54	53	54	54	53	52	53	53	52	52	50
			7.0	57	56	55	55	56	55	55	54	55	54	54	53	54	53	53	52	51
			10.0	57	56	56	56	56	55	55	55	55	54	54	54	54	53	53	52	52

