

屋内照明器具特性

| | | | |
|---------|----------------------------------------|--|--|
| 品番 (品名) | LGB16737 | | |
| 光源 | LLD40402CQ1 (SHUKOU) ×1 620.0 1 m | | |
| 管理番号 | K0184427 (0) DR 1 | | |
| BZ分類 | BZ1 | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|----------------|-----------------|------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率 | 69 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | 上方光束 1 % | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % |
| 下方光束 | 68 % | 床 | | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % |
| 室指数 | 照明率 (X 0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 53 | 48 | 45 | 43 | 53 | 48 | 45 | 43 | 52 | 47 | 44 | 42 | 51 | 47 | 44 | 42 | 41 |
| | 中 | 0.63 | 0.8 | 58 | 54 | 50 | 48 | 58 | 53 | 50 | 48 | 56 | 52 | 50 | 48 | 55 | 52 | 49 | 47 | 46 |
| | 否 | 0.56 | 1.0 | 61 | 57 | 54 | 52 | 61 | 57 | 54 | 51 | 59 | 56 | 53 | 51 | 58 | 55 | 53 | 51 | 50 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 64 | 60 | 57 | 55 | 63 | 60 | 57 | 55 | 62 | 59 | 56 | 54 | 60 | 58 | 56 | 54 | 53 |
| | | | 1.5 | 66 | 62 | 60 | 57 | 65 | 62 | 59 | 57 | 63 | 61 | 58 | 57 | 62 | 59 | 58 | 56 | 55 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 69 | 67 | 65 | 63 | 68 | 66 | 64 | 63 | 67 | 65 | 63 | 62 | 65 | 63 | 62 | 61 | 59 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 70 | 68 | 66 | 65 | 69 | 67 | 66 | 64 | 67 | 66 | 64 | 63 | 66 | 65 | 63 | 62 | 61 |
| Hm | 0.71Hm | 0.71Hm | 4.0 | 71 | 70 | 68 | 67 | 70 | 69 | 67 | 66 | 69 | 67 | 66 | 65 | 67 | 66 | 65 | 64 | 62 |
| | | | 5.0 | 72 | 71 | 69 | 68 | 71 | 70 | 69 | 68 | 69 | 68 | 67 | 66 | 68 | 67 | 66 | 65 | 63 |
| | | | 7.0 | 73 | 72 | 71 | 70 | 72 | 71 | 70 | 69 | 70 | 69 | 69 | 68 | 68 | 68 | 67 | 67 | 65 |
| | | | 10.0 | 73 | 73 | 72 | 71 | 72 | 72 | 71 | 71 | 71 | 70 | 70 | 69 | 69 | 69 | 68 | 68 | 66 |

