

# 屋内照明器具特性

|         |                 |          |
|---------|-----------------|----------|
| 品番 (品名) | LGB15108        |          |
| 光源      | LLD3020MLCE1 ×1 | 795.0 lm |
| 管理番号    | K0176254(0)DR1  |          |
| BZ分類    | BZ1             |          |

|        |         |                 |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 63%     | 天井              | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        | 上方光束    |                 | 0%          | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束   | 63%     | 床               | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 室指数    |         |                 | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良       | 0.67            | 0.6         | 5.2 | 4.8 | 4.5 | 4.3 | 5.1 | 4.7 | 4.5 | 4.3 | 5.0 | 4.7 | 4.5 | 4.3 | 5.0 | 4.7 | 4.5 | 4.3 | 4.2 |
|        | 中       | 0.63            | 0.8         | 5.5 | 5.2 | 4.9 | 4.7 | 5.5 | 5.1 | 4.9 | 4.7 | 5.4 | 5.1 | 4.9 | 4.7 | 5.3 | 5.0 | 4.8 | 4.7 | 4.6 |
|        | 否       | 0.56            | 1.0         | 5.8 | 5.4 | 5.2 | 5.0 | 5.7 | 5.4 | 5.2 | 5.0 | 5.6 | 5.3 | 5.1 | 5.0 | 5.5 | 5.3 | 5.1 | 5.0 | 4.9 |
| 下方投影面積 | 等価発光面積  | cm <sup>2</sup> | 1.25        | 6.0 | 5.7 | 5.4 | 5.3 | 5.9 | 5.6 | 5.4 | 5.3 | 5.8 | 5.5 | 5.4 | 5.2 | 5.7 | 5.5 | 5.3 | 5.2 | 5.1 |
|        |         |                 | 1.5         | 6.1 | 5.8 | 5.6 | 5.5 | 6.0 | 5.8 | 5.6 | 5.4 | 5.9 | 5.7 | 5.5 | 5.4 | 5.8 | 5.6 | 5.5 | 5.4 | 5.3 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5         | 6.4 | 6.2 | 6.0 | 5.9 | 6.3 | 6.1 | 6.0 | 5.9 | 6.2 | 6.0 | 5.9 | 5.8 | 6.0 | 5.9 | 5.8 | 5.7 | 5.6 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0         | 6.4 | 6.3 | 6.1 | 6.0 | 6.4 | 6.2 | 6.1 | 6.0 | 6.2 | 6.1 | 6.0 | 5.9 | 6.1 | 6.0 | 5.9 | 5.8 | 5.7 |
| Hm     | 0.46Hm  | 0.46Hm          | 4.0         | 6.5 | 6.4 | 6.3 | 6.2 | 6.5 | 6.3 | 6.2 | 6.1 | 6.3 | 6.2 | 6.1 | 6.1 | 6.2 | 6.1 | 6.0 | 6.0 | 5.8 |
|        |         |                 | 5.0         | 6.6 | 6.5 | 6.4 | 6.3 | 6.5 | 6.4 | 6.3 | 6.3 | 6.4 | 6.3 | 6.2 | 6.2 | 6.2 | 6.2 | 6.1 | 6.1 | 5.9 |
|        |         |                 | 7.0         | 6.6 | 6.6 | 6.5 | 6.4 | 6.6 | 6.5 | 6.4 | 6.4 | 6.4 | 6.4 | 6.3 | 6.3 | 6.3 | 6.3 | 6.2 | 6.2 | 6.0 |
|        |         |                 | 10.0        | 6.7 | 6.6 | 6.6 | 6.5 | 6.6 | 6.6 | 6.5 | 6.5 | 6.5 | 6.4 | 6.4 | 6.4 | 6.3 | 6.3 | 6.3 | 6.2 | 6.1 |

