

屋内照明器具特性

品番 (品名) **LGB16738**

光源 **LLD40402CQ1 (SHUKOU) ×1** 620.0 1 m

管理番号 **K0184429 (0) DR1**

BZ分類 **BZ1**

器具効率	66 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	1 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	65 %		壁	床	室指数	照明率 (X 0.01)	ZCM													
保守率	良 0.67	0.6	51	46	43	41	51	46	43	41	50	46	43	41	49	45	43	41	40	
	中 0.63	0.8	56	51	48	46	55	51	48	46	54	50	48	46	53	50	47	46	45	
	否 0.56	1.0	59	55	52	50	58	54	52	50	57	53	51	49	55	53	51	49	48	
下方投影面積	cm ²	1.25	61	58	55	53	60	57	55	53	59	56	54	52	58	55	53	52	51	
		1.5	63	60	57	55	62	59	57	55	60	58	56	54	59	57	55	54	53	
等価発光面積	cm ²	2.0	65	62	60	58	64	62	60	58	62	60	59	57	61	59	58	57	55	
		2.5	66	64	62	60	65	63	61	60	64	62	60	59	62	61	60	58	57	
取付高さ	器具間隔最大限		3.0	67	65	63	62	66	64	63	61	64	63	62	61	63	62	61	60	58
H m	0.69 H m	0.69 H m	4.0	68	66	65	64	67	66	65	63	66	64	63	62	64	63	62	61	60
			5.0	69	67	66	65	68	67	66	65	66	65	64	64	65	64	63	62	61
			7.0	69	68	68	67	69	68	67	66	67	66	66	65	65	65	64	64	62
			10.0	70	69	69	68	69	68	68	67	67	67	66	66	66	65	65	65	63

