

# 屋内照明器具特性

品番 (品名)	LGB16739				
光源	LLD4000LCB1 ×1                      845.0 lm				
管理番号	K0176218(0)DR1				
BZ分類	BZ5				

器具効率	64%	天井	80%				70%				50%				30%				0%		
	上方光束		2%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		62%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	3.6	2.8	2.3	1.9	3.5	2.7	2.2	1.9	3.3	2.6	2.2	1.9	3.1	2.5	2.2	1.9	1.7	
	中	0.63	0.8	4.2	3.4	2.9	2.5	4.1	3.4	2.9	2.5	3.9	3.3	2.8	2.5	3.7	3.2	2.8	2.5	2.3	
	否	0.56	1.0	4.6	3.9	3.4	3.0	4.5	3.8	3.3	3.0	4.2	3.7	3.3	2.9	4.0	3.6	3.2	2.9	2.7	
			1.25	5.0	4.3	3.9	3.5	4.8	4.3	3.8	3.5	4.6	4.1	3.7	3.4	4.4	4.0	3.6	3.3	3.2	
下方投影面積 等価発光面積			$\text{cm}^2$	1.5	5.2	4.6	4.2	3.8	5.1	4.6	4.1	3.8	4.9	4.4	4.0	3.7	4.6	4.3	3.9	3.7	3.5
			$\text{cm}^2$	2.0	5.6	5.1	4.7	4.4	5.5	5.0	4.6	4.3	5.2	4.8	4.5	4.2	5.0	4.7	4.4	4.2	4.0
			$\text{cm}^2$	2.5	5.8	5.4	5.0	4.7	5.7	5.3	5.0	4.7	5.5	5.1	4.8	4.6	5.2	5.0	4.7	4.5	4.3
取付高さ	器具間隔最大限			3.0	6.0	5.6	5.3	5.0	5.9	5.5	5.2	5.0	5.6	5.3	5.1	4.9	5.4	5.2	5.0	4.8	4.5
	Hm	1.15Hm	1.15Hm	4.0	6.2	5.9	5.6	5.4	6.1	5.8	5.6	5.3	5.8	5.6	5.4	5.2	5.6	5.4	5.3	5.1	4.9
				5.0	6.3	6.1	5.9	5.7	6.2	6.0	5.8	5.6	6.0	5.8	5.6	5.5	5.8	5.6	5.5	5.3	5.1
				7.0	6.5	6.3	6.1	6.0	6.4	6.2	6.0	5.9	6.1	6.0	5.9	5.7	5.9	5.8	5.7	5.6	5.4
				10.0	6.6	6.4	6.3	6.2	6.5	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	5.9	5.8	5.6

