

屋内照明器具特性

品番 (品名) **LGB16739**

光源 **LLD3020MLCE1 ×1** **795.0 lm**

管理番号 **K0176226(0)DR1**

BZ分類 **BZ1**

器具効率	73%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	73%		床	10%				10%				10%				10%				0%
		室指数	照明率 (×0.01)																ZCM	
保守率	良 0.67	0.6	58	52	49	47	57	52	49	47	56	52	49	47	55	51	48	46	46	
	中 0.63	0.8	62	58	54	52	62	57	54	52	60	57	54	52	59	56	53	52	51	
	否 0.56	1.0	65	61	58	56	65	61	58	55	63	60	57	55	62	59	57	55	54	
下方投影面積	cm ²	1.25	68	64	61	59	67	64	61	59	66	63	60	58	64	62	60	58	57	
		1.5	70	66	64	61	69	66	63	61	67	65	63	61	66	64	62	60	59	
等価発光面積	cm ²	2.0	72	69	67	65	71	69	66	65	70	67	66	64	68	66	65	63	62	
		2.5	73	71	69	67	72	70	68	67	71	69	67	66	69	68	67	65	64	
取付高さ	器具間隔最大限		3.0	74	72	70	69	73	71	70	68	72	70	69	68	70	69	68	67	65
	横方向 (A)	縦方向 (B)	4.0	75	74	72	71	75	73	72	71	73	72	71	70	71	70	69	69	67
Hm	0.50Hm	0.50Hm	5.0	76	75	74	72	75	74	73	72	74	73	72	71	72	71	70	70	68
			7.0	77	76	75	74	76	75	74	74	74	74	73	72	73	72	72	71	69
			10.0	78	77	76	76	77	76	75	75	75	74	74	73	73	73	73	72	70

